



INSTALLATION INSTRUCTIONS ELETECH SEPTIC TANKS

Protect your investment with correct preparation & installation

Excavate hole to required size as determined by the Owner's drainlayer

Place packing sand in hole to 100mm depth.

Screed 40mm slope – lower at inlet, higher at outlet

Lift tank using correct lifting gear

NOTE - DO NOT SHORT CHAIN THE UNITS, this will pull the swiftlifts out if angle is too steep

NEVER STAND BENEATH or IN THE PATH OF A RAISED LOAD

Place tank in hole with inlet towards house

MAKE SURE TANK RISER TOP is 50mm or more above ground level and is level – **USE A LEVEL**

Back-fill hole with packing sand or clean fill **COMPACTING EVERY 300mm.**

Repeat until up to ground level.

Ensure pipe connections are complete before covering

FILL TANK WITH WATER TO PREVENT FLOTATION

Place lids on tanks: **BE CAREFUL**- Lids are heavy

(bend your knees, do not use your back as a crane)

PLEASE NOTE

- 1| A permit from the responsible Local Authority will be required before installing an approved septic tank
- 2| The permit will require a licensed drainlayer to install the septic tank
- 3| Drainlayer does not have to be in attendance of delivery **BUT** will have to take responsibility for installation

FOR SALES & SERVICE PHONE
0800 ELE 222